## T1S R4W DUCHESNE COUNTY MONUMENT SURVEY RECORD SEC 4 | SEC 3 SEC 9 | SEC 10 U.S.B.&M. V - 13S 89°37'03" W 2641.38' 1/4 CORNER 5327.09 00°24'01" NOTE: THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT LOCATED AT LAT: 40°24'07.00259"N & LONG: 110°20'07.39032"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER NORTH

SECTION CORNER

## DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND MONUMENT SPIKE IN MONUMENT BOX AT SECTION CORNER

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

REFERENCED AS SHOWN

STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET) NAD 83 UTAH CENTRAL ZONE

N: 7322639.75 E: 1965696.09

**LATITUDE:** 40°25'00.12055" N

LONGITUDE: 110°19'54.26652" W

PUBLIC LAND SURVEY SYSTEM GCDB ID NO. UT300010S0040W0\_400600

## CERTIFICATION

<u>Jerry D. Allred</u> , Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date <u>8 FEB '16</u>

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor



NO SCALE